

APPENDIX 1

SPECIFICATIONS TABLES

MODEL	WATTS	VOLTS	PF	AMP	HZ	PH	ENGINE MODEL	ENGINE VOLTAGE	BATTERY BCI/CCA	FULL LOAD FUEL REQ.
DR20I4-A	20,000	120/240	1.0	83	60	1	ISUZU 4LE2	12 VOLTS	24/650	1.8 GAL
DR20I4-D	20,000	120/208	0.8	69	60	3	ISUZU 4LE2	12 VOLTS	24/650	1.8 GAL
DR20I4-J	20,000	120/240	0.8	60	60	3	ISUZU 4LE2	12 VOLTS	24/650	1.8 GAL
DR20I4-L	20,000	277/480	0.8	30	60	3	ISUZU 4LE2	12 VOLTS	24/650	1.8 GAL
DR45I4-A	45,000	120/240	1.0	187	60	1	IVECO NEF45 AMI	12 VOLTS	24/650	2.8 GAL
DR45I4-D	45,000	120/208	0.8	156	60	3	IVECO NEF45 AMI	12 VOLTS	24/650	2.8 GAL
DR45I4-J	45,000	120/240	0.8	135	60	3	IVECO NEF45 AMI	12 VOLTS	24/650	2.8 GAL
DR45I4-L	45,000	277/480	0.8	68	60	3	IVECO NEF45 AMI	12 VOLTS	24/350	2.8 GAL
DR65I4-A	65,000	120/240	1.0	270	60	1	IVECO NEF45 SM2	12 VOLTS	24/650	5.2 GAL
DR65I4-D	65,000	120/208	0.8	225	60	3	IVECO NEF45 SM2	12 VOLTS	24/650	5.2 GAL
DR65I4-J	65,000	120/240	0.8	195	60	3	IVECO NEF45 SM2	12 VOLTS	24/650	5.2 GAL
DR65I4-L	65,000	277/480	0.8	97	60	3	IVECO NEF45 SM2	12 VOLTS	24/650	5.2 GAL
DR90I4-A	90,000	120/240	1.0	375	60	1	IVECO NEF45 TM1X	12 VOLTS	31/900	6.8 GAL
DR90I4-D	90,000	120/208	0.8	312	60	3	IVECO NEF45 TM1X	12 VOLTS	31/900	6.8 GAL
DR90I4-J	90,000	120/240	0.8	270	60	3	IVECO NEF45 TM1X	12 VOLTS	31/900	6.8 GAL
DR90I4-L	90,000	277/480	0.8	135	60	3	IVECO NEF45 TM1X	12 VOLTS	31/900	6.8 GAL
DR130I4-A	130,000	120/240	1.0	541	60	1	IVECO NEF67 TE2X	12 VOLTS	31/900	8.9 GAL
DR130I4-D	130,000	120/208	0.8	451	60	3	IVECO NEF67 TE2X	12 VOLTS	31/900	8.9 GAL
DR130I4-J	130,000	120/240	0.8	390	60	3	IVECO NEF67 TE2X	12 VOLTS	31/900	8.9 GAL
DR130I4-L	130,000	277/480	0.8	195	60	3	IVECO NEF67 TE2X	12 VOLTS	31/900	8.9 GAL
DR175I4-A	175,000	120/240	1.0	729	60	1	IVECO NEF67 TE2X	12 VOLTS	4D/1200	10.9 GAL
DR175I4-D	175,000	120/208	0.8	607	60	3	IVECO NEF67 TE2X	12 VOLTS	4D/1200	10.9 GAL
DR175I4-J	175,000	120/240	0.8	526	60	3	IVECO NEF67 TE2X	12 VOLTS	4D/1200	10.9 GAL
DR175I4-L	175,000	277/480	0.8	263	60	3	IVECO NEF67 TE2X	12 VOLTS	4D/1200	10.9 GAL
DR200D4-D	200,000	120/208	0.8	607	60	3	DEUTZ BF4M1013FC	12 VOLTS	4D/1200	15.1 GAL
DR200D4-J	200,000	120/240	0.8	526	60	3	DEUTZ BF4M1013FC	12 VOLTS	4D/1200	15.1 GAL
DR200D4-L	200,000	277/480	0.8	263	60	3	DEUTZ BF4M1013FC	12 VOLTS	4D/1200	15.1 GAL
DR250I4-D	250,000	120/208	0.8	867	60	3	IVECO CURSOR 87 TE1D	24 VOLTS	(2) 4D/1200	16.3 GAL
DR250I4-J	250,000	120/240	0.8	751	60	3	IVECO CURSOR 87 TE1D	24 VOLTS	(2) 4D/1200	16.3 GAL
DR250I4-L	250,000	277/480	0.8	375	60	3	IVECO CURSOR 87 TE1D	24 VOLTS	(2) 4D/1200	16.3 GAL
DR300I4-D	300,000	120/208	0.8	1040	60	3	IVECO CURSOR 10 TE1D	24 VOLTS	(2) 4D/1200	21.3 GAL
DR300I4-J	300,000	120/240	0.8	902	60	3	IVECO CURSOR 10 TE1D	24 VOLTS	(2) 4D/1200	21.3 GAL
DR300I4-L	300,000	277/480	0.8	451	60	3	IVECO CURSOR 10 TE1D	24 VOLTS	(2) 4D/1200	21.3 GAL
DR350I4-D	350,000	120/208	0.8	1214	60	3	IVECO CURSOR 13 TE2X	24 VOLTS	(2) 4D/1200	22.2 GAL
DR350I4-J	350,000	120/240	0.8	1052	60	3	IVECO CURSOR 13 TE2X	24 VOLTS	(2) 4D/1200	22.2 GAL
DR350I4-L	350,000	277/480	0.8	526	60	3	IVECO CURSOR 13 TE2X	24 VOLTS	(2) 4D/1200	22.2 GAL
DR400V4-D	400,000	120/208	0.8	1390	60	3	VOLVO TAD1242GE-GS2	24 VOLTS	(2) 4D/1200	25.5 GAL
DR400V4-J	400,000	120/240	0.8	1204	60	3	VOLVO TAD1242GE-GS2	24 VOLTS	(2) 4D/1200	25.5 GAL
DR400V4-L	400,000	277/480	0.8	602	60	3	VOLVO TAD1242GE-GS2	24 VOLTS	(2) 4D/1200	25.5 GAL
DR500V4-J	500,000	120/208	0.8	1734	60	3	VOLVO TAD1641GE-GS2	24 VOLTS	(2) 4D/1200	32.2 GAL
DR500V4-L	500,000	277/480	0.8	751	60	3	VOLVO TAD1641GE-GS2	24 VOLTS	(2) 4D/1200	32.2 GAL
DR500V4-L	500,000	120/240	0.8	1503	60	3	VOLVO TAD1641GE-GS2	24 VOLTS	(2) 4D/1200	32.2 GAL
DR600V4-L	600,000	277/480	0.8	902	60	3	VOLVO TWD1643GE-GS3	24 VOLTS	(2) 4D/1200	43.0 GAL

Note: De-rate unit power ratings by 3-1/2 % per 1000 feet elevation above sea level.