

WINPOWER

'GP SERIES' ELECTRIC GENERATORS



GP5000B
with portability kit

BRIGGS & STRATTON ENGINE DRIVEN BRUSHLESS GENERATOR

► Four full featured sizes to choose from. Ruggedly built but light in weight for truly dependable portable power. Since 1925 Winpower has been providing quality standby electric systems for worldwide use. Coupling this low maintenance brushless generator to the durable long life B & S I/C engine is another winner from Winpower.

FEATURES:

- Briggs & Stratton I/C Engine
- Brushless Generator
- Full Wraparound Frame
- Vibration Isolators
- Circuit Breakers
- Copper Windings
- Sealed Ball Bearings
- Drip Proof Construction
- Superior Motor Starting
- Four Cycle Engine
- Fuel Gauge
- Low Tone Muffler
- Rewind Starter*
- Frame, Baked On Powder Coat
- Large Fuel Tank

*Except GP8000BS



WINPOWER

'GP SERIES' ELECTRIC GENERATORS

FEATURING

- ▶ **Totally brushless design.**

- ▶ **Voltage regulator capacitance type.**

- ▶ **Circuit breaker protection.**

- ▶ **Full wraparound frame.**

- ▶ **Large fuel tanks.**

- ▶ **Durable powder coat finish**

SPECIFICATIONS

MODEL	GP2500B	GP4000B	GP5000B	GP8000BS
Surge Rating	3000W	5500W	6400W	9500W
Continuous Rating	2500W	4000W	5100W	8000W
Voltage (Single Phase)	120V	120/240V	120/240V	120/240V
Frequency	60 HZ	60 HZ	60HZ	60 HZ
Outlets				
Standard 120/240	2/0	2/0	2/0	2/0
Twist Lock 120/240	0/0	1/1	1/1	1/1
Circuit Breakers	Standard	Standard	Standard	Standard
Capacitor Voltage Regulator	Standard	Standard	Standard	Standard
Motor Starting Ability (Code G Capacitor Start)	1 HP	1-1/2 HP	2-1/2 HP	4 HP
Full Wraparound Frame	Standard	Standard	Standard	Standard
Vibration Isolators	Standard	Standard	Standard	Standard
Portability Kit	N/A	Optional	Optional	Optional

ENGINE	Briggs & Stratton	Briggs & Stratton	Briggs & Stratton	Briggs & Stratton
Type	Air Cooled 4 Cycle I/C	Air Cooled 4 Cycle I/C	Air Cooled 4 Cycle I/C	Air Cooled 4 Cycle I/C
Model	132432	195432	254422	402447
Displacement	206 cc	319 cc	400 cc	656 cc
Horsepower (3600 RPM)	5 HP	8 HP	11 HP	16 HP (Twin)
Fuel Tank Capacity	3-1/2 Gal.	6 Gal.	6 Gal.	6 Gal.
Run Time - 1/2 load	9-1/2 hrs.	10 hrs.	8 hrs.	5-1/2 hrs.
Run Time - Full load	6-1/2 hrs.	7 hrs.	5-1/2 hrs.	3-1/4 hrs.
Fuel Gauge	Standard	Standard	Standard	Standard
Low Oil Shut Off	Standard	Standard	Standard	Standard
Start/Stop Switch	Standard	Standard	Standard	Standard
Econ-O-Mizer	N/A	Optional	Optional	N/A
Electric Start (12 volt)	N/A	Optional	Optional	Standard

DIMENSIONS AND WEIGHT

Length	24-1/2"	30"	30"	33"
Width	15"	19-1/2"	19-1/2"	25"
Height	22-1/4"	25-1/4"	25-1/4"	27"
Net Weight	83 lbs.	140 lbs.	163 lbs.	245 lbs.
Shipping Weight	90 lbs.	148 lbs.	171 lbs.	257 lbs.

Specifications are subject to change without notice.

AUTHORIZED WINPOWER DEALER



WINPOWER
Pierce Power Products
P.O. Box 2000
Upland, IN 46989
Phone (317) 998-7832